

Installation Guide for 2017-23 Tesla Model 3 LED Tail lights

ALPHAREX specializes in designing and producing superior and uniquely stylish aftermarket automotive performance lighting with unrivalled innovative technology. This installation guide takes you through the step-by-step process of installing your new **ALPHAREX TAIL LIGHTS** for your 2017-23 Tesla Model 3 **DO NOT USE DIELECTRIC GREASE!**



Table of Contents



PART I REMOVE TAIL LIGHTS

- **INSTALLATION TOOLS**
- **STEP 1.** Unplug & remove outer section of the tail lights
- **STEP 2.** Remove outer section of the tail lights
- **STEP 3.** Remove the trunk panel
- **STEP 4.** Remove inner section of the tail lights

PART II INSTALL ALPHAREX TAIL LIGHTS

- **STEP 1.** Install inner section of the tail lights
- **STEP 2.** Install outer section of the tail lights
- **STEP 3.** Complete Installation

Disclaimer: This installation article is a tutorial guide. By reading this article, you agree it is for reference only and AlphaRex USA and its distributors make no guarantee on the finished results. Under no circumstances whatsoever shall AlphaRex USA nor its distributors be liable for any damage, misuse or personal injuries. If you do not fully understand the installation procedure, it is highly recommended that you seek help from professional mechanics to do the installation.

PART I REMOVE TAIL LIGHTS

INSTALLATION TOOLS

PREPARE THESE TOOLS FOR INSTALLATION



Plastic
Panel
Popper



Metal
Panel
Popper



Wrench



1/4 Ratchet



1/4 Extension

8mm



Socket

Whenever working on your vehicle, always make sure your vehicle is OFF and parked.



STEP 1. UNPLUG & REMOVE OUTER SECTION OF THE TAIL LIGHTS


Open the trunk and begin by taking off the tail light cover on the driver's side.




Turn the plastic screw cover counterclockwise to remove it.



Open the side of the carpet and proceed to remove the two 8mm nuts from the back of the tail light.





Disconnect the tail light wires.



STEP 2. REMOVE OUTER SECTION OF THE TAIL LIGHTS



Open the charger port from the driver's side. Using plastic pliers, gently lift the edges of the tail light and pull it outward.



Completely detach and remove the outer section of the tail light.



Repeat the removal process for the other side.





STEP 3. REMOVE THE TRUNK PANEL

Using a plastic plier, gently pull and remove the trunk panel that is secured by multiple plastic clips.




If your Tesla Model 3 is equipped with a power liftgate trunk, ensure to unplug the wire while removing the trunk panel.






Take off the trunk panel and set it aside for future re-installation.



STEP 4. REMOVE INNER SECTION OF THE TAIL LIGHTS

Disconnect the inner section of the tail lights' wire for each side.



Unscrew and remove the 8mm bolt from the back of each tail light.





Using a plastic plier, delicately pull and detach the inner section of the tail lights.



PART II INSTALL ALPHAREX TAIL LIGHTS




STEP 1. INSTALL INNER SECTION OF THE TAIL LIGHTS

Align the ALPHAREX tail lights with the trunk and the corresponding mounting holes.




Reverse the removal process to install the new tail lights. Secure the 8mm bolts and reconnect the tail light wires. **DO NOT USE DIELECTRIC GREASE!**






Re-install the trunk panel and complete the installation of the inner tail lights.



STEP 2. INSTALL OUTER SECTION OF THE TAIL LIGHTS

Connect the tail light wires and secure the position onto the vehicle body. **DO NOT USE DIELECTRIC GREASE!** Follow the reverse of the removal process to finish the installation. Repeat the same steps for the other side.





STEP 3. COMPLETE INSTALLATION

Congratulations! You have completed the installation for ALPHAREX **17-23 Tesla Model 3 LED TAIL LIGHTS.**

